

# AN1804 4G INTERCOM & ACCESS CONTROL



The Aristel AN1804 4G Door intercom is a multi-function system designed to eliminate the cost of expensive cabling when installed at sites. The intercom uses a 4G SIM card and supports all networks, image includes optional SMB.

## Product Features

- Intercom can call up to 3 numbers sequentially.
- Remote access control of 2 gates or doors.
- Up to 1152 authorized guests can activate the door release by calling the intercom.
- IP65 rated stainless steel cabinet.
- Optional Vertical and Horizontal surface mount boxes available. Image includes vertical SMB

## Technical Information

### Intercom features

- 2 Relays for access control.
- Programmable timers for ring time, door open/closed time.
- Access control by up to 1152 authorized guests by free call to intercom.
- Intercom can be called for silent monitoring.

### Interconnect parameters

- input terminals for egress button
- 2 relays, each with NO/NC contacts .
- Inbuilt rectifier bridge enables AC or DC operation on 12-24 volts.
- Adjustable speaker and microphone levels.
- Network signal strength check by SMS .
- Operating temperature -20C to 50C .

### Security

- Administrator only has SMS and dial in access for changing settings.
- Log of guests' arrival times can be SMS to administrator.  
Phone lock for personal privacy protection; Admin/User 2-level configuration mode.

### Voice features

- High quality audio with noise cancelling algorithm. Speaker output >80dBA at 1 metre.

### Physical properties

- 1 hotline programmable button. (Speed dial, Intercom etc.);
- Operates on 12-24 volt AC or DC.
- Weight: 1.0Kg.
- Dimensions: 113w x 174h x 65d mm.

### Network Compatibility

All networks.	WCDMA	B1, B2, B5, B8,
	LTE FDD	B1, B2, B3, B4, B5, B7, B8, B28
	LTE TDD	B40
	GSM EDGE	QUAD BAND

### Product Certification



ISO 9001



#### SPECIFICATION:

Operating Voltage  
Operating Current  
RF Module  
Physical size  
Length of antenna tail  
Humidity  
Operating Temperature

#### AN1804 AUV-S

12 to 24 Volt AC/DC  
Maximum 250 mA, Typically 55mA  
QUECTEL - EC21AU  
Face plate: 170 x 100 mm, Stainless cabinet: 174 x 113 x 65 mm  
3 metre cable  
Less than 80% RH  
-20°C to 50°C

Distributed by:



Aristel Networks Pty Ltd  
1/25 Howleys Rd Notting Hill Vic 3168  
P: 03 8542 2300 F: 03 9544 3299  
Freecall: 1800 002 133  
[www.aristel.com.au](http://www.aristel.com.au)

**Aristel**