C-Bus®





5500PCU

The DIN rail mounted C-Bus USB PC Interface is a C-Bus system device designed to provide a gateway between a PC and C-Bus network.

Through the C-Bus USB PC Interface, C-Bus units can be programmed, commands can be issued to the C-Bus network and activity on the C-Bus network can be monitored.

The C-Bus USB PC Interface uses a USB Type B socket and allows a PC with USB output to be interfaced to a C-Bus system. A 1 metre Type A to Type B USB cable is provided to connect the 5500PCU to a PC.

Before you connect the 5500PCU to a PC you must install the USB PCI Driver. This is available from the downloads section of the Clipsal Integrated Systems (CIS) website (www. clipsal.com/cis).

The USB PC Interface can be programmed to generate the C-Bus system clock for communications data synchronisation on the C-Bus network and also provides a software selectable network burden. Installation of the C-Bus USB PC Interface on the C-Bus network requires connection to the Category 5 unshielded twisted pair C-Bus network cable. The connection to a personal computer is via the Type A to Type B USB cable provided with the unit, as per above.

The unit incorporates C-Bus and Unit/Communications LED indicators. These LEDs indicate if the unit is powered and functional, if sufficient C-Bus network voltage is available, if a valid C-Bus clock is present and if data transfer is currently taking place.

Like all the other units that make up a C-Bus system, the DIN Rail C-Bus USB PC Interface is Australian designed, developed and manufactured by Clipsal Australia Pty Ltd.

clipsal.com/cis



C-Bus® USB PC Interface 5500PCU

- Provides a gateway between a PC and a C-Bus Network via USB connection
- **DIN Rail mounted**
- 4 DIN modules wide
- Requires connection to a C-Bus network via an unshielded twisted pair C-Bus network cable
- 2 x RJ45 sockets provided for C-Bus connections
- Connection to a personal computer via a Type B socket located on the unit and a Type A to Type B USB cable (supplied)
- Capable of generating a C-Bus system clock for communications data synchronisation
- Provides a software selectable network burden
- Consumes 32mA from the C-Bus network
- Incorporates a Unit/Communications LED indicator
- Incorporates a C-Bus LED indicator
- Dimensions: W=72mm, H=92mm, D=63mm
- Weight 92g.

Product of Clipsal Australia Pty. Ltd.

A member of the Schneider Electric Group

Head Office

12 Park Terrace, Bowden South Australia 5007 PO Box 103 Hindmarsh South Australia 5007

+61 8 8345 9500 Telephone +61 8 8346 0845 Facsimile Internet www.clipsal.com/cis E-Mail cis@clipsal.com.au

CIS Technical Support Hotline:

1300 722 247

Customer Service Enquiries:

1300 2025 25

National Customer Service Facsimile: 1300 2025 56

International Enquiries

International Sales and Marketing

+61 8 8269 058 Telephone Facsimile +61 8 8340 7350 E-Mail export@clipsal.com.au

New Zealand

Clipsal Industries (NZ) Ltd Telephone +64 9 576 3403

Malaysia

Clipsal Integrated Systems (M) Sdn Bhd Telephone +60 3 7665 3555

Singapore

Clipsal Integrated Systems Pte Ltd Telephone +65 6415 3232/3233

China

Clipsal China Limited Telephone +86 755 8237 5959

Greece

Schneider Electric AE Telephone +30 69 4646 3200

Hong Kong

Clipsal Integrated Systems (HK) Limited Telephone +852 2487 0261

Schneider Electric India Pvt Ltd Telephone +91 11 5159 0000

Indonesia

PT Clipsal Graha Nusa Telephone +62 21 630 6430

Korea Clipsal Korea Co. Ltd

Telephone +82 549 5550 Pakistan

Clipsal Pakistan (Pvt) Ltd Telephone +92 21 506 7278 **Philippines**

Clipsal Phillipines Inc Telephone +632 683 0275-78 South Africa

Clipsal South Africa (Pty) Ltd Telephone +27 11 314 5200

Taiwan

Clipsal (Taiwan) Co Ltd Telephone +886 2 2558 3456

Thailand

Clipsal Thailand Ltd Telephone +66 2 952 5338-42 United Arab Emirates

Clipsal Middle East

Telephone +971 6 5570 777

United Kingdom

Clipsal Integrated Systems C/o Schneider Electric Telephone +44 870 608 8 608

Vietnam Clipsal - VTEC Telephone +848 856 3002



Clipsal Australia Ptv Ltd reserves the right to change specifications. modify designs and discontinue items without incurring obligation and whilst every effort is made to ensure that descriptions, specifications and other information in this catalogue are correct, no warranty is given in respect thereof and the company shall not be liable for any error therein.

© Clipsal Australia Pty Ltd.

The identified trademarks and copyrights are the property of Clipsal Australia Pty Ltd unless otherwise noted.



CLIPCOM 13731 Aug 2007 O/N 11827