

C-Bus Indoor PIR Movement Sensor



5751L Series

The C-Bus Indoor PIR Movement Sensor is a C-Bus input unit used to detect movement by sensing natural thermal radiation emitted from any moving body. When movement is detected, the unit issues commands over the C-Bus network to control C-Bus output devices. The sensor is suitable for controlling lighting in homes, apartments, offices, corridors, conference rooms, etc.

The sensor incorporates the C-Bus 'Learn Mode' feature. Learn mode allows the units to be programmed without the need for a PC connected to the system. Alternatively, the units can be programmed via a PC using the installation software.

The sensor has a detection field that covers an area up to 8.5 metres from the unit, with a field of view of 90°. The unit features a 'lenseless' design with 12 overlapping zones forming a continuous detection field. Therefore, uniform sensitivity is achieved across the whole of the detection field, with no dead zones. This feature allows for wall or ceiling mounting of the sensor.

The sensor is capable of controlling up to four C-Bus 'Group Addresses', with each being controlled for a different period if required.

An added feature is that each sensor includes an ambient light level sensor (Sunset Switch) feature, which automatically turns lights on when the ambient light level falls below the threshold level (at sunset), and then turns the lights off again at sunrise. Alternatively, the lights can be programmed to automatically turn off at a set time after sunset.

A light emitting diode (LED) on the sensor head can be programmed to turn on when movement is detected. This enables easy positioning and commissioning of the sensor.

The unit initiates a regular status report, which compares the status of all input and output units within the same C-Bus 'Application Address'. If a state disagreement exists between the output units and the input units the C-Bus Indoor PIR Movement Sensor will change its internal state to suit the output.

Like all other units that make up a C-Bus system, the C-Bus Indoor PIR Movement Sensor is Australian designed, developed and manufactured by Clipsal Integrated Systems Pty Ltd.

clipsal.com/cis

5751L Series C-Bus Indoor PIR Movement Sensor

- Capable of controlling up to four C-Bus 'Group Addresses', with each being controlled for a different period if required.
- Incorporates an ambient light level sensor which acts as a Sunset Switch to control the status of the load.
- A light emitting diode (LED) on the sensor head can be programmed to turn on when movement is detected, via the installation software, enabling easy positioning and commissioning of the sensor.
- Time-out variation from 1 second to 18 hours, 12 minutes and 15 seconds, is set via the installation software.
- Light sensitivity variation from one lux to full sunlight is set via an adjustment screw located on the sensor unit.
- The detection field that covers an area up to 8.5 metres from the unit, with a field of view of 90°.
- Lens less design with 12 overlapping zones forming a continuous detection field.
- An electrostatic and electromagnetic shield around the sensor elements reduces false triggering from radio frequency interference (RFI).
- Utilizes high performance pyroelectric ceramic sensors with excellent signal to noise ratio.
- An optical bandpass filter minimises unwanted light and heat sources triggering the circuitry.
- Dual element detectors minimise false triggering from rapid environmental temperature changes.
- Refer to 5751L Installation Instruction for location and mounting details.
- Available in Australian and export version.
- Wall or ceiling mounted.
- Designed to meet Australian and European standards for EMC Compliance and Safety.
- Configured via either the C-Bus Installation Software or via the C-Bus Learn Enabled feature.
- An inbuilt non-volatile memory retains programmed information relating to the current operating status of the unit in the event of a power failure.
- Communication with other C-Bus devices and the C-Bus supply voltage is obtained via a single C-Bus twisted pair cable.
- Initiates a regular status report, which compares the status of all input and output units within the same C-Bus 'Application Address'.



Head Office

12 Park Terrace, Bowden, South Australia 5007
Telephone (08) 8269 0560
International +61 8 8269 0560
Facsimile (08) 8346 0845
International +61 8 8346 0845
E-Mail cis@clipsal.com.au
Internet clipsal.com/cis

International Enquiries

Head Office Export Department

Telephone +61 8 8269 0587
Facsimile +61 8 8340 7350
E-Mail export@clipsal.com.au
Internet clipsal.com

New Zealand

Clipsal Industries (NZ) Ltd
Telephone +64 9 576 303

Malaysia

Clipsal Integrated Systems (M) Sbn Bhd
Telephone +60 3 7665 3555

Singapore

CIS Pte Ltd (Singapore)
Telephone +65 266 1998

Hong Kong

Clipsal Integrated Systems (HK) Limited
Telephone +852 2 487 0261

China

Clipsal China Limited
Telephone +86 755 246 1122

Taiwan

Clipsal (Taiwan) Co Ltd
Telephone +886 2 25583456

Thailand

Clipsal Thailand Ltd
Telephone +66 2 952 5338

South Africa

Clipsal South Africa (Pty) Ltd
Telephone +27 11 314 5200

United Kingdom

Clipsal Ltd (UK)
Telephone +44 1494 521 111

Greece

Clipsal Hellas S.A.
Telephone +30 1 993 9165

