

## scenix series SX

- in wall main and surround speaker
- compact design
- dual 130mm bass drivers
- fits on standard 90mm stud framework

The Scenix loudspeaker is modelled around the award winning Acoustix MK2 bookshelf speaker. The symmetrical, three driver, two way design provides greater intelligibility and transparency across the frequency range, even when positioned close to the listener.

The high frequency drive unit is a 26mm (1") dual concentric diaphragm with wave guide centre plug for controlled directivity and a smooth, revealing upper treble.

Dual 130mm (5¼") bass drivers with 25mm (1") vented magnet voice coils provide an exceptionally smooth response with low distortion.

A sealed enclosure keeps the cabinet dimensions compact. Offering LF extension to 80Hz, this speaker will truly excel when paired with a complementary subwoofer. The Scenix will fit between standard stud framework and has a depth of only 97mm, making it a versatile choice in most wall cavities.

\*Black grille version available

Please consult your dealer for complementary speaker recommendations.



### specifications scenix

Frequency Range	80Hz - 40kHz (-10dB)
Power Handling	50 - 150 Watts RMS recommended amplifier power
Sensitivity	91dB SPL - 2.83V at 1m half space
Impedance	6 Ohms
Configuration	Double woofer 5 inch 2-way
Crossover Point	2.1kHz
Bass Driver(s)	Fibre reinforced polymer basket, 130mm (5¼") doped paper cone driver, 25mm (1") vented magnet voice coil wound on high temperature aluminium former
High Frequency Driver	26mm (1") dual concentric diaphragm with waveguide centre plug for controlled directivity. Non-reflective dual chambered magnet structure with copper shorting ring to lower distortion
Enclosure Type	Sealed with internal bracing
Dimensions	470mm high x 295mm wide x 97mm deep cabinet 535mm high x 360mm wide x 1.6mm thick faceplate 475mm high x 300mm wide recommended cutout
Weight	10kg

