

# STAGE FRONT

HOME THEATER SOLUTIONS™

DATA SHEET



## IW/2550LCR

PROFESSIONAL QUALITY, IN-WALL,  
LEFT/CENTER/RIGHT CHANNEL LOUDSPEAKER



ENGINEERED BY



## In-wall Left/Center/Right Channel Loudspeaker

IW2550LCR

Stock Number

FG01330



### Features

- Dual 5.25" Injection-molded TCC™ (Talc, Carbon, and Ceramic-filled) cone woofers are extremely rigid to reduce breakup, lower distortion and provide enhanced bass response
- 1" fluid-cooled Teteron® dome tweeter delivers ultra-wide dispersion and silky-smooth high-frequency response
- Cross-braced ported cabinet with integrated frame design fits standard 2X4 construction and is easily retrofitted
- Gold plated input terminals accept 12 gauge wire and ensure positive connections
- Epoxy-coated MicroPerf™ grille provides an elegant yet unobtrusive appearance

### Specifications

- Frequency Response: 80Hz to 20kHz +/-3dB
- Sensitivity: 88dB (2.83V@1 meter)
- Hole Cutout Dimensions: 19 7/8 inches X 9 3/8 inches
- Depth from Front of wall: 3 7/8 inches
- Recommended Amplifier Power: 15 to 125 Watts
- Impedance: 6 ohm nominal; 3.2 ohm minimum

**Warranty: Lifetime limited**

**Shipping Weight: 17.63 lbs, 8.0 kg**

### Loudspeaker Dimensions

